DECLARATION OF PERFORMANCE
No. 4

1. Unique identification code of the product-type:

00031/3021 Paint for interior use

2. Type, batch or serial number or any other element allowing identification of the construction product:

Semi-matt wall paint IGIS 20. Tinklu str. 33-1, Panevezys

3. Technical specification applicable to the construction product:

Company standard **ĮST 147203777-29:2017**

4. Intended use or uses of the construction product, in accordance with the applicable technical specification, as foreseen by the manufacturer:

Semi matt water-based pure acrylic paint for interior use. For interior walls and ceilings made of mineral construction materials (plaster, plasterboard, filled surfaces, wallpaper, brick masonry, concrete, etc.). Excellent for walls and ceilings in intensively operated residential and public premises that requires frequent cleaning - corridors, stairwells, kitchens, schools, medical, food companies, etc.

5. Name, registered trade name or registered trade mark and contact address of the manufacturer:

Sole Proprietorship of I. Krisciunas "IGIS", Tinklu str. 33-1, LT-35115 Panevezys, Lithuania

6. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks:

Does not apply

7. System or systems of assessment and verification of constancy of performance of the construction product for STR 1.01.04:2015 Regulation Section V:

System 2+

8. In case of the declaration of performance concerning a construction product covered by a:

Production control certificate Nr. SPSC-9397 issued by NB 1397 VĮ "Statybos produkcijos sertifikavimo centras".

9. Declared performance:

Essential characteristics	**Performance**	**Technical Specification**
Surface-drying time (20±2) ºC, min	≤ 60	EN ISO 9117-3
Liquid water permeability W, kg/(m^2*$h^{0,5}$)	Class W2 (medium)	EN 1062-3 EN 1062-1
Water vapour permeability V, g/m^2*d	Class V2 (medium)	EN ISO 7783 EN 1062-1
The loss of thickness of the coat (after 200 scrubs), µm	< 5 (class 1)	EN ISO 11998-3 EN 13300+AC
Hiding power:	hiding power class 1, with a spreading rate of 6 m^2 /l	EN ISO 6504-3 A method
Resistance to liquids: 5 % soda solution 1 % dodecyldimethylammonium chloride 1 % chloramin B 2 % chlor clean Isopropyl alcohol	0 (S0) after 24 hours there are no changes	EN ISO 2812-1 (A method) EN ISO 4628-1 EN ISO 4628-2

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 5.

Signed for and on behalf of the manufacturer by:

Arturas Aputis Director of Commerce

Sole Proprietorship of I. Krisciunas “IGIS“

Tinklu str. 33-1, LT-35115 Panevezys, Lithuania

19-01-2021