## PRODUCT DATA SHEET

# **IGIS TEX**

# Primer before decorative plaster

- · Improves adhesion
- Evens out the absorption
- · Easy to apply
- · Ensures even drying
- Forms a vapor permeable layer
- · Environment and health friendly

#### USE

Acrylic copolymer primer for interior use. Intended to enhance the adhesion of decorative plaster, structural paint, liquid wallpaper or filling concrete or plaster surfaces.

#### SURFACE PREPARATION

The surface must be dry, withstanding loads, stable and clean. Fresh concrete layer may be primed not earlier than after 14 days and must be completely firm.

PRIMING		
Stir well before and during use. Apply one coat of the primer.		
Work Tools:	brush, roller, airless spraying gun	
Tool cleaning:	with water	
Application conditions:	+10 °C to +25 °C and (35–80) % relative humidity	
Coverage rate:	4-5 m <sup>2</sup> /I	
Drying time (20°C, 65% RH):	2 - 2.5 hours	

## UTILISATION

Do not pour into drains, water or soil. Empty, dry product package should be recycled or utilised according to national law.



#### TECHNICAL DATA

Purpose:	for interior use
Binder:	acrylic copolymer
Solvent:	water
Color:	white or colored
Density (20°C):	(1,62 - 1,65) g/cm <sup>3</sup>
pH (20°C):	8,0 - 9,0
Volatile organic compound (VOC):	< 2 g/I EN ISO 11890-2
Formaldehyde concentration in the tare:	VdL-RL 03: 6 ppm or (6x10 <sup>-4</sup> ) %
Classification by maximum grain size:	Coarse (to 1500 μm) EN 13300
Volume solids:	~ 50,0 %
Resistance to static water (23±2 °C, 24h):	after 24 hours defect rating 0 EN ISO 2812-2; EN ISO 4628-1
Shelf life:	tightly sealed packaging - 24 months from date of manufacture on the packaging
Packing:	1I, 3I, 10I buckets

#### ADDITIONAL INFORMATION

The information above is based on laboratory tests and practical experience, and has been validated from the date indicated on the product data sheet. The manufacturer reserves the right to make technical changes. The manufacturer is not liable for damage caused by using the product not in accordance with the instructions or for improper purposes.

